





# Shanghai Shengjie Bearing Co., Ltd.

## TYPE TS



## Timken EE790114 790223D Tapered roller bearing

Bearing No. EE790114

EE790114 Bearing 2D drawings and 3D CAD models

Series	790000
Cone Part Number	EE790114
Design Units	Imperial
Cage Type	Pin-Type
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>	1210000 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup>	314000 lbf
d	11.5000 in
B - Cone Width	5.3750 in
R - Cone Backface To Clear Radius <sup>3</sup>	0.25 in
da - Cone Frontface Backing Diameter	13.5 in
db - Cone Backface Backing Diameter	13.78 in
Ab - Cage-Cone Frontface Clearance	0.34 in
Aa - Cage-Cone Backface Clearance	0.75 in
a - Effective Center Location <sup>4</sup>	-0.96 in
C90 - Dynamic Radial Rating (90 million revolutions) <sup>5</sup>	180000 lbf
C1 - Dynamic Radial Rating (1 million revolutions) <sup>6</sup>	695000 lbf



## Shanghai Shengjie Bearing Co., Ltd.

C0 - Static Radial Rating	923000 lbf
C <sub>a90</sub> - Dynamic Thrust Rating (90 million revolutions) <sup>7</sup>	122000 lbf
K - Factor <sup>8</sup>	1.48
G1 - Heat Generation Factor (Roller-Raceway)	2660
G2 - Heat Generation Factor (Rib-Roller End)	170
Cg - Geometry Factor	0.190