



# Shanghai Shengjie Bearing Co., Ltd.

## TYPE TS



## Timken LM281049 LM281010CD Tapered roller bearing

Bearing No. LM281049

LM281049 Bearing 2D drawings and 3D CAD models

Series	LM281000
Cone Part Number	LM281049
Design Units	Imperial
Cage Type	Pin-Type
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>	1840000 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup>	477000 lbf
d	25.4375 in
B - Cone Width	5.5625 in
R - Cone Backface To Clear Radius <sup>3</sup>	0.25 in
da - Cone Frontface Backing Diameter	26.69 in
db - Cone Backface Backing Diameter	26.93 in
Ab - Cage-Cone Frontface Clearance	0.36 in
Aa - Cage-Cone Backface Clearance	0.44 in
a - Effective Center Location <sup>4</sup>	0.12 in
C90 - Dynamic Radial Rating (90 million revolutions) <sup>5</sup>	274000 lbf
C1 - Dynamic Radial Rating (1 million revolutions) <sup>6</sup>	1060000 lbf



## Shanghai Shengjie Bearing Co., Ltd.

C0 - Static Radial Rating	2330000 lbf
C <sub>a90</sub> - Dynamic Thrust Rating (90 million revolutions) <sup>7</sup>	156000 lbf
K - Factor <sup>8</sup>	1.76
G1 - Heat Generation Factor (Roller-Raceway)	14763
G2 - Heat Generation Factor (Rib-Roller End)	920.6
Cg - Geometry Factor	0.315